

# Prediction of Aeroelastic Stability Using Computational Fluid Dynamics

K.J.Badcock, M.A.Woodgate, G.S.L.Goura,  
A.Moosa, G.N.Barakos, B.E.Richards  
Computational fluid dynamics laboratory,  
University of Glasgow

Work supported by BAE SYSTEMS, QinetiQ, EPSRC, Chevening Trust

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE <b>26 JUL 2004</b>		2. REPORT TYPE <b>N/A</b>		3. DATES COVERED <b>-</b>	
4. TITLE AND SUBTITLE <b>Prediction of Aeroelastic Stability Using Computational Fluid Dynamics</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>Computational fluid dynamics laboratory, University of Glasgow</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release, distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>See also ADM001685, CSP 02-5078, Proceedings for Aerodynamic Issues of Unmanned Air Vehicles (UAV)., The original document contains color images.</b>					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT <b>UU</b>	18. NUMBER OF PAGES <b>16</b>	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

# UAV Context

- Control system and flexibility integrated
- High rate motions
- Unusual design – unusual aerodynamics  
(B2 residual pitch problem)
- Places strain on linear aeroelastic methods
  - RANS based tools needed

# Holy Grail of Non-linear Aeroelasticity

- Diminish/remove unfavourable effects
  - LCO even a stable one has fatigue issues
  - Control system interactions (buzz?)
- Increase/exploit favourable effects
- Move from analysis into design
  - Non conservative designs
  - Possible higher performance

# Fluid Structure Interaction

- Model the time dependent aerodynamics
- Model the deforming structure under load
- Match the aerodynamics loads + structural deformations in time
- Transfer the loads + displacements information


# Aerodynamic Model Requirements

- RANS needed to capture large scale features
  - Still expensive, textbook MG required?
  - Validation of vortical flows
  - Prediction of flow separation (onset and progression)
  - Reduction via POD or ROM
- Small geometric features important
  - Vg's and riblets (hybrid / unstructured?)
- Active control requirements
  - Fully understand unsteady flows
  - Multi-disciplinary process

# Time Domain Simulation

- CFD-CSD model sequencing resolved
  - Staggered schemes, sub-iterations
- Inter-grid transformation can be a problem
  - CVT method is simple and effective, other methods can alter the dynamics
  - “Knowledge” based transformations. Total force and moment conservation + geometric constraints
  - Depends on structural model ( Stick models )
- Volume grid deformation resolved
  - TFI, springs...

# MDO Test Case – Influence of Transformation






# Conclusion on Time Marching

- Predictions of vortical flow effects need to be validated
- Transformation between grids needs care
- Calculations are costly
  - Suitable for analysis of isolated points
  - Unsuitable for design and certification

# Direct Calculation

- Unfavourable effects can be described mathematically
  - LCO is a Hopf bifurcation
- Add these conditions in the system of ODE's
  - This system is larger and much harder to solve
  - Only have to solve it once
  - Can play all sorts of steady CFD tricks
- Can only pick one type at a time
- What does non convergence mean?





# Solution of Augmented System


$$\begin{bmatrix}
 A & 0 & 0 & \mathbf{R}_\mu & 0 \\
 (\mathbf{A}\mathbf{P}_1)_w & A & I\omega & (\mathbf{A}\mathbf{P}_1)_\mu & -\mathbf{P}_2 \\
 (\mathbf{A}\mathbf{P}_2)_w & -I\omega & A & (\mathbf{A}\mathbf{P}_2)_\mu & \mathbf{P}_1 \\
 0 & \mathbf{S}^T & 0 & 0 & 0 \\
 0 & 0 & \mathbf{S}^T & 0 & 0
 \end{bmatrix} \times \Delta \begin{bmatrix} \mathbf{w} \\ \mathbf{P}_1 \\ \mathbf{P}_2 \\ \mu \\ \omega \end{bmatrix} = - \begin{bmatrix} \mathbf{R} \\ \mathbf{A}\mathbf{P}_1 + \omega\mathbf{P}_2 \\ \mathbf{A}\mathbf{P}_2 - \omega\mathbf{P}_1 \\ \mathbf{S}^T \mathbf{P}_1 \\ \mathbf{S}^T \mathbf{P}_2 - 1 \end{bmatrix}$$

Symmetric problem

# Results

- NACA0012 aerofoil
- C-grid, 128x32





# Evaluation

- Cost
  - Complete boundary in 2700s
  - Time marching calculation >5600s per point
  - Linear solver needs work
    - Preconditioner
    - Optimise code
- Generality
  - Build in equilibrium calculation as outer loop
  - Build in flight mechanics equations (PUMA)

# Conclusions

- Efficient tools with right level of modelling needed for fully integrated design of unusual vehicles
- Time marching developing towards useful tool for simulation of problematic conditions
- Tools (maybe direct method) needed for general design and certification purposes
- Could we limit the physical modelling in some regions of the design space to make current tools applicable now?
- Methods need to integrate all sources of data into model



# Outlook

- How valid are statements of stability based on modal damping?
- How do we integrate measurements and predictions in manner required at the moment?
- If high fidelity simulation is available in what ways will this influence the designs?